



# RF-TX1-915

Portable Radio Frequency  
Transmitter 915MHz



CONTACTA RADIO FREQUENCY

The RF-TX1-915 Portable Transmitter delivers wireless transmission of speech and/or music to users through the RF-RX1-915 Portable Receivers, using the 915MHz frequency.

It's a wireless assistive listening system intended for guided tours or interpretation services using FM radio waves.

## Key Features

- › Transmission range up to 100 meters/328 feet in open air
- › Unlimited number of Receivers that can be used per group
- › Digital audio transmission technology
- › Frequency bandwidth of 70Hz - 12kHz providing excellent sound quality for both speech and music
- › 25 selectable channels
- › White Backlit LCM
- › Selectable Auto-Lock feature
- › Micro USB power supply for fast and simple charging
- › Compatible with the RF-DC-24 Charging case and the RF-DC6 Charging Station for easy drop-in charging
- › Exclusive software suite for fast group programming



## Applications

This wireless assistive listening system can be used in venues, such as:

- › Museums
- › Historical Sites
- › Exhibitions/Events/Conferences
- › Any space where guided tours take place

## Includes

- › Lanyard
- › RF-TX1-LM, Lapel Microphone
- › Micro USB Power Cable and USB Wall Mount Charger
- › x2 AA 1.2V 2100mA rechargeable (NiMH) batteries

## Compatible Accessories

- › RF-RX1-915, Portable Receiver
- › RF-DC-24, 24 Bay Charging Case
- › RF-DC-6, 6 Bay Charging Station
- › RF-TX1-EM, Ear-Worn Microphone
- › RF-TX1-LM, Lapel Microphone

contacta

Phone: (616) 392-3400  
Email: sales@contactainc.com  
www.contactainc.com

## Compliance

- › Trade Agreement Act (TAA) Compliant
  - Federal Acquisition Regulation (FAR) 52.225-5 Trade Agreement
  - (made in a TAA compliant country)
- › Americans with Disabilities Act (ADA) Compliant - USA

## Physical Data

Dimensions	Height – 3.46" Width – 2.51" Depth – 1.14"
Weight	0.25lbs
Finish	Mixed

## Technical Data

Emission Modulation	4GFSK
Latency	<4 ms@HQ
Mic Capsule	Condenser
RF Output Power	High: 8±2 dBm Low: 5±3 dBm
Frequency Band	915 ~ 928 MHz
Antenna	Flexible Connector
Mic Input	3-pole Mini XLR
Audio Input	3.5mm
Batteries	x2 AA 1.2V 2100mA rechargeable (NiMH)
Battery Life	>8 hours
Transmission Range	Up to 100m / 328ft
Frequency Response	70Hz - 12kHz
Channel	25 simultaneous channels
Display	White Backlit LCM
Selectable Features	Auto-on / Auto-lock
Software	Smart programming software for fast set up of multiple receivers