SoundPlus[™] TV Infrared Listening System • Model WIR 238

Description:


The WIR 238 is ideal for TV listening, meetings, or any small group listening application. Listen at the volume of your comfort without disturbing others. The system connects directly to your TV, VCR, or DVD equipped with standard output jacks. It features high quality, low distortion sound, and angled ear couplings for maximum comfort and performance. On/Off switch is built into the "arms" of the receiver, so it can never be left on to drain the batteries.

Applications:

• Television Listening • Stereo Listening • Small Group Listening • Language Interpretation • Offices

WIR TX238 Transmitter:

Size, Weight, Color:	6.25" L x 3.25" W x 1.25" H (15.9 cm x 8.3 cm x 3.2 cm), 5.1 oz (140 g), Gray
Power Input:	12 VDC (center is positive) on DC connector, 200 mA Class II wall transformer
	TFP 024 Power Supply: North America: 120 VAC, 60 Hz, UL/CSA
	TFP 032 Power Supply, 2 pin Euro mains plug, 230 VAC, 50-60 Hz, CE
	TFP 033 Power Supply, 3 pin UK mains plug, 230 VAC, 50-60 Hz, CE
Subcarrier Frequency:	2.3 MHz, 2.8 MHz, or stereo
Range:	30ft (9m) line-of-site
Auto Power On/Off:	Transmitter shuts off infrared after 5 minutes when audio signal is removed. Battery charging
	functions remain on full time.
Microphone Input:	3.5 mm jack for MIC 084 Electret TV Microphone, 1.5 k Ω
Line Inputs:	2 RCA jacks for mono or stereo line-level sources. 200 mV min. to 10 V rms max. input level, 5.1 k $_{ m M}$
Automatic Level Control:	35 dB compression range
Infrared LEDs, Pattern:	6 IR LEDs, 45 degree cone-shaped coverage pattern to 6 dB intensity, 30 ft (9 m) line of sight
Charging Ports:	Charges one WIR RX238 Receiver plus two additional BAT AP97A NiMH battery packs**
Approvals:	RoHS, WEEE
Warranty:	5 years, parts and labor*



TX238 Front

TX238 Rear

*90 days on accessories.

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE!




SoundPlus[™] TV Infrared Listening System • Model WIR 238

WIR RX238 Receiver:

Weight: Material and Color: Battery Type, Life: Modulation Frequency: Frequency Response: Signal-to-Noise Ratio: Controls:

Acoustic Output: Compatibility:

Power Switch: Ear Pads: Approvals: Warranty: 2.1 oz (60 g) with battery ABS plastic, Black and Grey BAT AP97A NiMH Battery Pack, 6 hours 2.3 and 2.8 MHz 200 Hz to 8 kHz, ± 5 dB 60 dB at 10 m Volume control thumbwheel; screwdriver adjust balance and (L & R) tone controls 112 dB MAX SSPL90 with 2 cc coupler Compatible with transmitters operating on 2.3 MHz/2.8 MHz Built into receiver "arms" Uses EAR 031 foam cushions ROHS, WEEE 5 years, parts and labor*



RX238 Front

*90 days on accessories.

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE!

WILLIAMS SOUND® Helping People Hear