# Installation and operations manual Weather Alert Strobe Model X68-S

#### General

The Silent Call Weather Alert Strobe is designed to be used with a Midland weather radio that has an external jack. It may function with other brands but correct operation cannot be guaranteed.

### **Operation**

Plug the X68-S cord into the external output jack on the weather radio. Plug the X68-S power supply into a 120VAC output.

In operation, the X68-S will begin flashing whenever the unit goes into alarm. It will remain flashing until either the alert times out or until you cancel the alarm.

The weather radio also includes the ability to test the siren and the X68-S. On the weather radio, press the PROGRAM button. Then scroll down through the program options until you reach "SIREN TEST (P 8)". Press the ENTER button and the siren will sound and the X68-S will begin to flash. Press the STOP button to cancel the test. Note that testing the siren and the X68-S only indicates that the X68-S is functional and is connected correctly. It does not test the S.A.M.E. programming. To program the radio for your county or counties, please consult the WEATHER RADIO manual.

## **Technical Support**

For technical support on this or any other Silent Call product, please feel free to contact us. You can reach us by phone at 800-572-5227 (voice or TTY) or by Email at <a href="mailto:support@silentcall.com">support@silentcall.com</a>

## **Limited Warranty**

Your X68-S is warranted to be free of defects in material and workmanship for one year from the date of initial purchase. During that time, the unit will be repaired or replaced free of charge when shipped prepaid to Silent Call Communications. To obtain warranty service, contact Silent Call to obtain a return material authorization. This warranty is void if the defect is caused by customer abuse or neglect.

**X68-S** Technical specifications:

Operates on 2- AAA batteries, not included

